

Details Gipskassetten

Lochung	Größe	Lochflächenanteil Kassette	Lochflächenanteil nach DIN	umlaufend ungelochter Rand		
				SK	Tegular	Tegular S
RL 6/15	Modul 600	11,0%	12,6%	31,0 mm	26,5 mm	31,0 mm
	Modul 625	10,7%	12,6%	36,0 mm	31,5 mm	36,0 mm
RL 6/18	Modul 600	7,7%	8,7%	32,5 mm	28,0 mm	32,5 mm
	Modul 625	7,5%	8,7%	36,0 mm	31,5 mm	36,0 mm
RL 8/18	Modul 600	13,6%	15,5%	31,5 mm	27,0 mm	31,5 mm
	Modul 625	13,4%	15,5%	35,0 mm	30,5 mm	35,0 mm
RL 10/23	Modul 600	12,5%	14,8%	38,5 mm	34,0 mm	38,5 mm
	Modul 625	12,5%	14,8%	39,5 mm	35,0 mm	39,5 mm
RL 12/25	Modul 600	15,0%	18,1%	40,5 mm	36,0 mm	40,5 mm
	Modul 625	15,2%	18,1%	40,5 mm	36,0 mm	40,5 mm
RL 15/30	Modul 600	17,3%	19,6%	34,0 mm	29,5 mm	34,0 mm
	Modul 625	17,7%	19,6%	31,5 mm	27,0 mm	31,5 mm
V 8/12/50	Modul 600	11,4%	13,1%	28,0 mm	23,5 mm	28,0 mm
	Modul 625	10,5%	13,1%	40,5 mm	36,0 mm	40,5 mm
V 12/20/66	Modul 600	15,5%	19,6%	39,0 mm	34,5 mm	39,0 mm
	Modul 625	14,3%	19,6%	51,5 mm	47,0 mm	51,5 mm
QL 3mm	Modul 600	11,5%	13,0%	32,6 mm	28,1 mm	32,6 mm
	Modul 625	11,5%	13,0%	32,6 mm	28,1 mm	32,6 mm
QL 8/18	Modul 600	17,4%	19,8%	31,5 mm	27,0 mm	31,5 mm
	Modul 625	17,0%	19,8%	35,0 mm	30,5 mm	35,0 mm
QL 12/25	Modul 600	19,1%	23,0%	40,5 mm	36,0 mm	40,5 mm
	Modul 625	19,3%	23,0%	40,5 mm	36,0 mm	40,5 mm