

LED-Quattro-Line

Luminaire with micro-prisms-glass cover IP65




Dimension drawing: module L = 600/625

clip-in/hinge down luminaire type KK
with bevel




clip-in/hinge down luminaire type KK
sharp edged



Lay-in-luminaire type EK
with bevel



Lay-in-luminaire type EK
sharp edged



Lay-in-luminaire type EKA



Lay-in-luminaire type EKP



Technical characteristics:

Voltage:	220 - 240 V, 50 - 60 Hz
Protection class:	I
Protective system:	IP 65
Colour index:	840 - high colour rendering
Electric power:	35 W
device life cycle:	50 000 h
inclusive emergency lighting:	possible for safety lighting installation according to EN 50172
Control gear:	LED-Driver directly mounted to the luminaire housing, dimmable on request, device life cycle up to 100.000h RST2013K1-S 15 10SW
Connection:	3-pin plug-in system prefabricated supplied with connection cable
Case:	galvanized steel, powder coated, match to the ceiling system
Distribution of light:	by use of Micro-prisms-diffuser consisting of acrylic glass PMMA
Case:	galvanized steel, powder coated, match to the ceiling system
LED-Luminaires:	suitable for lighting of computer screen workplaces according to EN12464-1
Delivery:	pre finished
Luminaire luminousflux:	3349 lm
Colour Temperature/ Luminous Colour:	4000K/neutral white